

05-25-00

A

05/24/00

JC622 U.S. PTO

Please type a plus sign (+) inside this box [+]

Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))		Attorney Docket No.	4191-00014	Total Pages	177
		First Named Inventor or Application Identifier			
		KENNETH PAWSON			
		Express Mail Label No.	E1582775539US		
APPLICATION ELEMENTS See MPEP chapter 600 concerning utility patent application contents		ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, D.C. 20231			
1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)		6. <input type="checkbox"/> Microfiche Computer Program (Appendix)			
2. <input checked="" type="checkbox"/> Specification [Total Pages 11] (preferred arrangement set forth below) <ul style="list-style-type: none"> - Descriptive title of the Invention - Cross References to Related Applications - Statement Regarding Fed sponsored R & D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure 		7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ul style="list-style-type: none"> a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identify of above copies 			
3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets 1]		ACCOMPANYING APPLICATION PARTS			
4. Oath or Declaration [Total Pages 6] <ul style="list-style-type: none"> a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below] <ul style="list-style-type: none"> i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b). 					
5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked). The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.		8. <input type="checkbox"/> Assignment Papers (cover sheet & document(s))			
		9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input type="checkbox"/> Power of Attorney (when there is an assignee)			
		10. <input type="checkbox"/> English Translation Document (if applicable)			
		11. <input checked="" type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input checked="" type="checkbox"/> Copies of IDS Citations			
		12. <input type="checkbox"/> Preliminary Amendment			
		13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized)			
		14. <input type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, Status still proper and desired			
		15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed)			
		16. <input checked="" type="checkbox"/> Other: <u>Certificate of Express Mail</u>			
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No.: _____ / _____					
18. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label		<div style="border: 1px solid black; padding: 5px; width: fit-content;"> Insert Customer No. or Attach bar code label here </div>		or <input checked="" type="checkbox"/> Correspondence address below.	
NAME	MICHAEL E. TAKEN (Reg. No. 28,120)				
	ANDRUS, SCEALES, STARKE & SAWALL, LLP				
ADDRESS	100 East Wisconsin Avenue				
	Suite 1100				
CITY	Milwaukee	STATE	Wisconsin	ZIP CODE	53202-4178
COUNTRY	U.S.A.	TELEPHONE	(414) 271-7590	FAX	(414) 271-5770

CERTIFICATE OF EXPRESS MAIL

This is to certify that this correspondence is being deposited with the United States Postal Service as EXPRESS MAIL POST OFFICE TO ADDRESSEE in an envelope addressed to Commissioner of Patents and Trademarks, Washington D.C., 20231 on May 24, 2000. The Express Label is EL582775539US.

Dawn M. Oleszak

Name

May 24, 2000

Date

Dawn M. Oleszak

Signature

5-24-00

Date

SPACE EFFICIENT EXHAUST AFTERTREATMENT FILTER

Inventors: Kenneth Pawson

William C. Haberkamp

Attorney Docket No.: 4191-00014

Andrus, Sceales, Starke & Sawall
100 East Wisconsin Avenue, Suite 1100
Milwaukee, WI 53202
Phone: (414) 271-7590
Telefax: (414) 271-5770

SPACE EFFICIENT EXHAUST AFTERTREATMENT FILTER BACKGROUND AND SUMMARY

The invention relates to the packaging of mufflers and exhaust components for internal combustion engines, and more particularly to an exhaust
5 aftertreatment filter, including catalytic devices, that need to be fit into a limited space.

The invention arose during development efforts directed toward minimizing the space required for an exhaust aftertreatment filter, and maximizing the usable area of a filter or catalytic element. The invention also arose during development efforts attempting to accommodate different types of exhaust system configurations
10 without necessitating a complete redesign of the exhaust aftertreatment filter housing. The present invention meets these and other needs in a particularly simple and effective manner.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an illustration of a space inefficient exhaust aftertreatment filter.

15 Fig. 2 is an illustration of a space efficient exhaust aftertreatment filter, and is taken along line 2-2 of Fig. 3.

Fig. 3 is a side sectional view of an exhaust aftertreatment filter in accordance with the invention.

DETAILED DESCRIPTION

20 Fig. 1 shows a space inefficient exhaust aftertreatment filter 10 including a cylindrical housing 12, an exhaust filter element 14, such as a catalytic element, and a return or transfer tube 16. This type of arrangement can be used where it is desired to have both the inlet and outlet on the same end of the filter housing, rather than opposing ends. Exhaust from the engine flows to the filter inlet then into the page in Fig. 1
25 through catalytic filter element 14 and then reverses direction and flows out of the page through return tube 16 to the outlet of the filter. In the example in Fig. 1, return tube 16 has a 5 inch outer diameter, and filter housing 12 has an 18 inch inner diameter, with half inch clearance. This leaves space for an 11.5 inch round substrate catalytic filter element 14 having an area of 103.9 square inches.

30 Fig. 2 shows a space efficient exhaust aftertreatment filter 20 including housing 22, catalytic exhaust filter element 24, and transfer or return tube 26. Using the

same dimensions as in Fig. 1, i.e. housing 22 has an 18 inch inner diameter and transfer tube 26 has a 5 inch outer diameter, the area of catalytic filter element 24 can now be increased to 198.7 square inches. This ninety-one percent increase in surface area of the catalytic filter element is attained without increasing the size of the filter housing, i.e.

- 5 filter housings 22 and 12 have the same diameter, yet catalytic filter element 24 has ninety-one percent more cross sectional area than catalytic filter element 14.

Fig. 3 shows housing 22 extending axially along an axis 28 between distally opposite first and second ends 30 and 32. A first port 34 is provided at first end 30 of the housing, and a second port 36 is also provided at first end 30 of the housing.

- 10 One of the ports is an inlet, and the other port is an outlet. In the embodiment of Fig. 3, port 34 is the inlet receiving exhaust from engine 38, and port 36 is the outlet. Housing 22 has an intermediate section 38 between distally opposite ends 30 and 32. The intermediate section 38 has a cross sectional area $A1$ along sectional plane 2-2 transverse to axis 28. Exhaust filter element 24 is in intermediate section 38 and entirely
15 fills the noted cross sectional area $A1$ except for a smaller cut-out 40 in exhaust filter element 24 of cross sectional area $A2$. Exhaust filter element 24 has a cross sectional area $A3 = A1 - A2$. Transfer or return tube 26 extends through cut-out 40 and communicates with port 36. Port 34 communicates with exhaust filter element 24. Exhaust flows axially as shown at arrows 42 through exhaust filter element 24 between
20 first and second distally opposite sides 44 and 46 thereof. First side 44 faces first end 30 of the housing, and second side 46 faces second end 32 of the housing. Exhaust flows axially as shown at arrow 48 through transfer tube 26 through cut-out 40 in the opposite axial direction, i.e. in the orientation of Fig. 3, axial flow 42 is leftwardly, and axial flow 48 is rightwardly. The outer periphery of exhaust filter element 24 is sealed at insulative
25 sealing material 50 to housing 22, and the inner periphery of filter element 24 at cut-out 40 is sealed at insulative sealing material 52 to transfer tube 26, such that all exhaust flow passes through exhaust filter element 24 without bypass.

- First side 44 of exhaust filter element 24 communicates with first port 34. Second end 32 of housing 22 is closed, and exhaust flow reverses axial direction as
30 shown at arrow 54 at second end 32 of the housing. Second side 46 of exhaust filter element 24 communicates through the noted flow reversal at 54 and transfer tube 26

through cut-out 40 with second port 36. Cut-out 40 is axially aligned with port 36. First side 44 of exhaust filter element 24 is axially aligned with port 34. In an alternate embodiment, first port 34 may be non-aligned with first side 44 such that the exhaust flow direction changes between first port 34 and first side 44. In another embodiment, exhaust flow between the first port and the first side of the exhaust filter element may include a radial component, relative to axis 28, at the first port, and an axial component at the first side of the exhaust filter element, to be described. Housing 22 includes a sidewall 56 extending axially between distally opposite first and second end walls 58 and 60. Both of the first and second ports 34 and 36 may extend through first end wall 58, as shown in Fig. 3. In alternate embodiments, one or both of first and second ports 34 and 36 may extend through sidewall 56 at a location between first side 44 of exhaust filter element 24 and first end wall 58, for example as shown in dashed line at 34a and 36a, respectively, providing the above noted radial flow components for example as shown in dashed line at 42a and 48a, respectively. These alternatives still enable both the inlet and the outlet to be at the same axial end of the housing. In preferred form, the first port 34 or 34a is the inlet, and the second port 36 or 36a is the outlet, such that first side 44 of exhaust filter element 24 is an upstream dirty side, and second side 46 of exhaust filter element 24 is a downstream clean side. In an alternate embodiment, the second port 36 or 36a is the inlet, and the first port 34 or 34a is the outlet, such that second side 46 of exhaust filter element 24 is an upstream dirty side, and first side 44 of exhaust filter element 24 is a downstream clean side.

In the preferred embodiment, housing 22 is cylindrical, and transfer tube 26 extends centrally axially in the housing and defines a central flow channel within transfer tube 26, and defines an annular flow channel within housing 22 and concentrically surrounding transfer tube 26 and the central flow channel therein. Catalytic exhaust filter element 24 is provided as an annular member in the noted annular flow channel and having a central cut-out 40 receiving transfer tube 26 therethrough. Exhaust both enters and exits housing 22 at first end 30 at inlet 34 or 34a and outlet 36 or 36a, respectively. Exhaust flows axially through the noted annular flow channel and exhaust filter element 24 in one axial direction such as 42, and exhaust flows axially through the noted central flow channel and transfer tube 26 and cut-out 40

- in the opposite axial direction such as 48. Further in the preferred embodiment, second end 32 of housing 22 is closed by a removable cover 62 attached to housing 22 by threads, clamps, or the like, schematically shown at 64. Removal of cover 62 permits inspection and removal of exhaust filter element 24 from housing 22 without
- 5 disassembling the exhaust system, for example without disassembling inlet 34 from housing 22 and without disassembling outlet 36 from housing 22.

It is recognized that various equivalents, alternatives and modifications are possible within the scope of the appended claims.

5
CLAIMS

What is claimed is:

1. An exhaust aftertreatment filter comprising a housing extending axially along an axis between distally opposite first and second ends, a first port at said first end of said housing, a second port also at said first end of said housing, one of said first and second ports being an inlet, the other of said first and second ports being an outlet, said
5 housing having an intermediate section between said distally opposite ends, said intermediate section having a given cross-sectional area $A1$ along a sectional plane transverse to said axis, an exhaust filter element in said intermediate section and entirely filling said given cross-sectional area $A1$ except for a smaller cut-out in said exhaust filter element of cross-sectional area $A2$, said exhaust filter element having a cross-
10 sectional area $A3 = A1 - A2$, a transfer tube extending through said cut-out and communicating with said second port, said first port communicating with said exhaust filter element, wherein exhaust flows axially through said exhaust filter element between first and second distally opposite sides of said exhaust filter element, said first side facing said first end of said housing, said second side facing said second end of said
15 housing, wherein exhaust flows axially through said exhaust filter element in one axial direction, wherein exhaust flows axially through said transfer tube through said cut-out in the opposite axial direction.

2. The invention according to claim 1 wherein said exhaust filter element has an outer periphery sealed to said housing, and has an inner periphery at said cut-out and sealed to said transfer tube, such that all exhaust flow passes through said exhaust filter element without bypass.

3. The invention according to claim 1 wherein:

said first side of said exhaust filter element communicates with said first port;

5 said second end of said housing is closed, and exhaust flow reverses axial direction at said second end of said housing;

said second side of said exhaust filter element communicates through said flow reversal and said transfer tube through said cut-out with said second port.

4. The invention according to claim 3 wherein said cut-out is axially aligned with said second port.

5. The invention according to claim 3 wherein said first side of said exhaust filter element is axially aligned with said first port.

6. The invention according to claim 3 wherein exhaust flow direction changes between said first port and said first side of said exhaust filter element.

7. The invention according to claim 6 wherein exhaust flow between said first port and said first side of said exhaust filter element includes a radial component, relative to said axis, at said first port, and an axial component at said first side of said exhaust filter element.

8. The invention according to claim 3 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein both of said first and second ports extend through said first end wall.

9. The invention according to claim 3 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein one of said first and second ports extends through said sidewall at a location between said first side of said exhaust filter element and said first end wall, and the other of said first and second ports extends through said first end wall.

10. The invention according to claim 9 wherein said first port extends through said sidewall, and said second port extends through said first end wall.

11. The invention according to claim 3 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein said first port extends through said sidewall at a first location between said first side of said exhaust filter element and said first end wall, and said second port extends through said sidewall at a second location between said first side of said exhaust filter element and said first end wall.

12. The invention according to claim 3 wherein said first port is said inlet, and said second port is said outlet, such that said first side of said exhaust filter element is an upstream dirty side, and said second side of said exhaust filter element is a downstream clean side.

13. The invention according to claim 3 wherein said second port is said inlet, and said first port is said outlet, such that said second side of said exhaust filter element is an upstream dirty side, and said first side of said exhaust filter element is a downstream clean side.

14. The invention according to claim 3 wherein said second end of said housing is closed by a removable cover permitting inspection and removal of said exhaust filter element from said housing without disassembling said inlet from said housing and without disassembling said outlet from said housing.

15. The invention according to claim 3 wherein said exhaust filter element is a catalytic element.

16. An exhaust aftertreatment filter comprising a housing extending axially along an axis between distally opposite first and second ends, a first port at said first end of said housing, a second port also at said first end of said housing, one of said first and second ports being an inlet, the other of said first and second ports being an outlet, said second end of said housing being closed, a transfer tube extending axially in said housing and defining a central flow channel within said transfer tube, and defining an annular flow channel within said housing and concentrically surrounding said transfer tube and said central flow channel therein, an annular exhaust filter element in said annular flow channel, said annular exhaust filter element having a central cut-out receiving said transfer tube therethrough, wherein exhaust both enters and exits said housing at said first end at said inlet and said outlet, respectively, and wherein exhaust flows axially through said annular flow channel and said exhaust filter element in one axial direction, and wherein exhaust flows axially through said central flow channel and said transfer tube and said cut-out in the opposite axial direction.

17. The invention according to claim 16 wherein exhaust flows axially in said annular flow channel through said exhaust filter element between first and second distally opposite sides of said exhaust filter element, said first side facing said first end of said housing having both of said first and second ports, said second side facing said second closed end of said housing, said exhaust flow reversing axial direction at said second closed end of said housing.

18. The invention according to claim 17 wherein said cut-out is axially aligned with said second port.

19. The invention according to claim 17 wherein said first side of said exhaust filter element is axially aligned with said first port.

20. The invention according to claim 17 wherein exhaust flow direction changes between said first port and said first side of said exhaust filter element.

21. The invention according to claim 20 wherein exhaust flow between said first port and said first side of said exhaust filter element includes a radial component, relative to said axis, at said first port, and an axial component at said first side of said exhaust filter element.

22. The invention according to claim 17 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein both of said first and second ports extend through said first end wall.

23. The invention according to claim 17 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein one of said first and second ports extends through said sidewall adjacent said first end wall, and the other of said first and second ports extends through said first end wall.

24. The invention according to claim 23 wherein said first port extends through said sidewall, and said second port extends through said first end wall.

25. The invention according to claim 17 wherein said housing includes a sidewall extending between distally opposite first and second end walls, and wherein said first port extends through said sidewall adjacent said first end wall, and said second port extends through said sidewall adjacent said first end wall.

26. The invention according to claim 17 wherein said first port is said inlet, and said second port is said outlet, such that said first side of said exhaust filter element is an upstream dirty side, and said second side of said exhaust filter element is a downstream clean side.

27. The invention according to claim 17 wherein said second port is said inlet, and said first port is said outlet, such that said second side of said exhaust filter element is an upstream dirty side, and said first side of said exhaust filter element is a downstream clean side.

28. The invention according to claim 17 wherein said second end of said housing is closed by a removable cover permitting inspection and removal of said exhaust filter element from said housing without disassembling said inlet from said housing and without disassembling said outlet from said housing

29. The invention according to claim 17 wherein said exhaust filter element is a catalytic element.

SPACE EFFICIENT EXHAUST AFTERTREATMENT FILTER

ABSTRACT OF THE DISCLOSURE

An exhaust aftertreatment filter (20) includes a housing (22) extending axially along an axis (28) between distally opposite first and second ends (30 and 32), a first port (34) at the first end of the housing, a second port (36) also at the first end of the housing, one of the first and second ports being an inlet, and the other being an outlet, the housing having an intermediate section (38) between the distally opposite ends, the intermediate section having a given cross sectional area $A1$ along a sectional plane transverse to the axis, a catalytic exhaust filter element (24) in the intermediate section and entirely filling the cross sectional area $A1$ except for a smaller cut-out (40) in the exhaust filter element of cross sectional area $A2$, the exhaust filter element having a cross sectional area $A3 = A1 - A2$, a transfer tube (26) extending through the cut-out and communicating with the second port. Exhaust flows axially (42) through the exhaust filter element between first and second distally opposite sides (44 and 46) of the exhaust filter element, the first side facing the first end of the housing, the second side facing the second end of the housing, exhaust flowing axially through the exhaust filter element in one axial direction (42) and flowing through the transfer tube and cut-out in the opposite axial direction (48).






Figure 1

Figure 2



Type a plus sign (+) inside this box [+]

Approved for use through 9/30/98

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

PTO/SB/01 (8/96) <div style="text-align: center;">DECLARATION</div> <div style="display: flex; justify-content: space-around;"><div>Declaration <input checked="" type="checkbox"/> Submitted with Initial Filing</div><div>OR</div><div>Declaration <input type="checkbox"/> Submitted after Initial Filing</div></div>	<table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 60%;">Attorney Docket Number</td><td>4191-00014</td></tr><tr><td>First Named Inventor</td><td>Kenneth Pawson</td></tr><tr><td colspan="2" style="text-align: center;">COMPLETE IF KNOWN</td></tr><tr><td>Application Number</td><td></td></tr><tr><td>Filing Date</td><td></td></tr><tr><td>Group Art Unit</td><td></td></tr><tr><td>Examiner Name</td><td></td></tr></table>	Attorney Docket Number	4191-00014	First Named Inventor	Kenneth Pawson	COMPLETE IF KNOWN		Application Number		Filing Date		Group Art Unit		Examiner Name																			
Attorney Docket Number	4191-00014																																
First Named Inventor	Kenneth Pawson																																
COMPLETE IF KNOWN																																	
Application Number																																	
Filing Date																																	
Group Art Unit																																	
Examiner Name																																	
<p>As a below named inventor, I hereby declare that:</p> <p>My residence, post office address, and citizenship are as stated below next to my name.</p> <p>I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:</p> <div style="border: 1px solid black; padding: 5px; text-align: center; margin: 5px 0;">SPACE EFFICIENT EXHAUST AFTERTREATMENT FILTER</div> <p style="text-align: center;">(Title of the Invention)</p> <p>the specification of which <input checked="" type="checkbox"/> is attached hereto</p> <p>OR</p> <p><input type="checkbox"/> was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).</p> <p>I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.</p> <p>I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56.</p> <p>I hereby claim foreign priority benefits under Title 35, United States Code §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.</p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th rowspan="2">Prior Foreign Application Number(s)</th><th rowspan="2">Country</th><th rowspan="2">Foreign Filing Date (MM/DD/YYYY)</th><th rowspan="2">Priority Not Claimed</th><th colspan="2">Copy Attached?</th></tr><tr><th>YES</th><th>NO</th></tr></thead><tbody><tr><td rowspan="5"></td><td rowspan="5"></td><td rowspan="5"></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr></tbody></table> <p><input type="checkbox"/> Additional foreign application numbers are listed on a supplemental priority sheet attached hereto:</p> <p>I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.</p> <table border="1" style="width: 100%; border-collapse: collapse;"><thead><tr><th style="width: 30%;">Application Number(s)</th><th style="width: 30%;">Filing Date (MM/DD/YYYY)</th><th style="width: 40%;">Additional provisional</th></tr></thead><tbody><tr><td></td><td></td><td><input type="checkbox"/> Application numbers are listed on a supplemental priority sheet attached hereto.</td></tr></tbody></table>		Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Copy Attached?		YES	NO				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Application Number(s)	Filing Date (MM/DD/YYYY)	Additional provisional			<input type="checkbox"/> Application numbers are listed on a supplemental priority sheet attached hereto.
Prior Foreign Application Number(s)	Country					Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Copy Attached?																									
		YES	NO																														
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																												
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																												
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																												
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																												
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																												
Application Number(s)	Filing Date (MM/DD/YYYY)	Additional provisional																															
		<input type="checkbox"/> Application numbers are listed on a supplemental priority sheet attached hereto.																															

Type a plus sign (+) inside this box [+]

DECLARATION			
<p>I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code §112. I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.</p>			
U.S. Parent Application Number	PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
<input type="checkbox"/> Additional U.S. or PCT international application numbers are listed on a supplemental priority sheet attached hereto.			
<p>As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:</p>			
Name	Registration Number	Name	Registration Number
Glenn O. Starke	17,031	Edward R. Williams, Jr.	36,057
Eugene R. Sawall	17,431	Joseph D. Kuborn	40,689
Daniel D. Fetterley	20,323	Mathew E. Corr	45,434
George H. Solveson	25,927	William L. Falk	27,709
Gary A. Essmann	29,376		
Thomas M. Wozny	28,922		
Michael E. Taken	28,120		
Joseph J. Jochman, Jr.	25,058		
Andrew S. McConnell	32,272		
<input type="checkbox"/> Additional attorney(s) and/or agent(s) named on a supplemental sheet attached hereto.			
<input checked="" type="checkbox"/> Please direct all correspondence to: Name MICHAEL E. TAKEN			
Address Andrus, Sceales, Starke & Sawall, LLP			
Address 100 East Wisconsin Avenue, Suite 1100			
City Milwaukee	State Wisconsin	Zip 53202-4178	
Country United States	Telephone (414) 271-7590	Fax (414) 271-5770	
<p>I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.</p>			
Name of Sole or First Inventor: <input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name KENNETH	Middle Initial --	Family Name PAWSON	Suffix e.g., Jr. --
Inventor's Signature		Date	
RESIDENCE: City Northampton	State	Country UK	Citizenship United Kingdom
POST OFFICE ADDRESS Mill House, East Haddon			
City Northampton	State	Zip NN6 8DU	Country United Kingdom
<input checked="" type="checkbox"/> Additional inventors are being named on supplemental sheet(s) attached hereto.			

Please type a plus sign (+) inside this box [+]

DECLARATION				ADDITIONAL INVENTOR(S) Supplemental Sheet			
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name	WILLIAM	Middle Initial	C.	Family Name	HABERKAMP	Suffix e.g., Jr.	--
Inventor's Signature	<i>William C. Haberkamp</i>			Date	<i>18 May 2000</i>		
RESIDENCE: City	Cookeville	State	TN	Country	USA	Citizenship	USA
POST OFFICE ADDRESS	511 North Dixie Avenue						
City	Cookeville	State	TN	Zip	38501	Country	USA